

Save



NEO SERIES® 8000

The NEO SERIES® 8000 library from Overland Storage delivers unmatched storage capability for organizations with very large amounts of mission-critical data. NEO 8000's award-winning architecture is designed to support the demanding requirements of SAN backup and archive operations, providing users with the benefits of increased data protection, enhanced data availability and the lowest possible cost of ownership.

Proven Technology

The NEO architecture has been chosen by thousands of major corporations worldwide as their library-technology-of-choice due to its robust, flexible, reliable design and enterprise-class capability. NEO 8000 capitalizes on that experience and takes a leap forward by bringing more capacity, faster performance and higher data availability to large data centers.

Enterprise-Class Performance and Capacity

Available in both SCSI and native Fibre Channel configurations, the NEO 8000 provides the capacity and speed required by today's high-performance SAN environments. Designed to accommodate industry leading LTO tape technology, the NEO 8000 provides access to as much as 1.6 PB of storage at over 21 TB/hour.*

Cost-Effective Scalability

No matter what the size of your data center, it is likely experiencing rapid growth in data storage requirements as you move to SAN functionality and consolidate multiple data centers. The NEO 8000 is designed to accommodate those changes by easily scaling from as few as 60 to as many as 1,000 cartridges, and from one to 24 tape drives.

Simplified Manageability

Overland makes managing your library more convenient by providing remote management capability with Overland's WebTLC technology. WebTLC, a remote library management tool embedded in the NEO, allows you to securely view and manage the library and all of its functions from any location that's convenient for you via an internet browser. The NEO 8000's built-in diagnostic capabilities proactively monitor and manage your backup and archive process, and notify you via emails and pages with library operation status, minimizing costly downtime.

Flexible Connectivity

Regardless of whether your data center storage applications require SCSI, Fibre Channel or iSCSI connectivity to optimize performance, the NEO 8000 has the solution that's right for you. Utilizing Overland's V.I.A.™ (Virtual Interface Architecture) technology, your network or SAN can easily communicate with the NEO 8000 tape library, by using one or more of the V.I.A. cards installed in the unit's rear-panel card cages.

Maximized Availability

Your data center likely demands zero downtime. The NEO 8000 provides multiple redundancy features to ensure that your data is always available. Hot-swap tape drives and power supplies ensure non-disruptive replacement. The NEO 8000's redundant power feature ensures that your library is protected against power failures. Proactive system monitoring and user-alerts ensure that potential points of failure are addressed in a way that minimizes the impact to your productivity. The NEO 8000's advanced diagnostics capability ensures that repair time is minimized. The end result is a reduction in the resources needed to reliably manage your backup and archive process and improve reliability and data availability.

Investment Protection

The NEO 8000 provides the ultimate in investment protection. NEO's industry-leading density means you benefit from more storage capacity per square foot than any other data center-class library on the market, mimizing the use of costly data center space. NEO's partitioning capability allows you to re-define the library into several smaller libraries, providing multi-server, multi-platform access, supporting backup consolidation and allowing you to allocate the cost of the library across your entire data center.

Service You Can Count On

NEO 8000 support includes 5x9x24 on-site service, with a highly-trained worldwide service team dedicated to supporting each system installation. A thorough site survey and pre-installation support is included in the purchase price, and professional installation services are provided. Verification of proper system operation is conducted before an installation is complete.

Experience You Can Trust

With 25 years of experience in data protection solutions, and expertise in both disk and tape technologies, Overland meets the needs of IT professionals worldwide by delivering D2D and D2D2T solutions that optimize the data backup, recovery and archive process. With award-winning designs, patented technologies, superior reliability, first-class sales and support, and a variety of solutions to meet a number of different needs, Overland Storage is the right choice for your data protection needs.



- Up to 1.6 PB capacity
- Up to 21 TB/hour performance
- LVD SCSI or native Fibre Channel
- Intelligent data management
- Superior density
- Up to 1000 cartridges; Up to 24 tape drives



Simply Protected

NEO SERIES® 8000 Specifications

MODELS	powered by  LTO-4			powered by  LTO-3		
	Base Configuration	Maximum Configuration	Scaled Configuration	Base Configuration	Maximum Configuration	Scaled Configuration
DRIVES AND MEDIA • Drive type • Media type	LTO-4 Ultrium 4	LTO-4 Ultrium 4	LTO-4 Ultrium 4	LTO-3 Ultrium 3	LTO-3 Ultrium 3	LTO-3 Ultrium 3
LIBRARY CONFIGURATION • Number of cartridges • Number of drives • Number of mailslot cartridges	100 1-12 15	500* 1-12 15	1000 1-24 30	100 1-12 15	500 1-21 15	1000 1-24 30
STORAGE CAPACITY • Native capacity • Compressed capacity • Native capacity of each 80-slot scalability kit (5 max.) • Compressed capacity of each 80-slot scalability kit (5 max.)	80 TB 160 TB 64 TB 128 TB	400 TB 800 TB n/a n/a	800 TB 1.6 PB n/a n/a	40 TB 80 TB 32 TB 64 TB	200 TB 400GB n/a n/a	400 TB 800 TB n/a n/a
SYSTEM PERFORMANCE • Native performance (Min. # drives installed) • Native performance (Max. # drives installed) • Compressed performance (Min. # drives installed) • Compressed performance (Max. # drives installed)	432 GB/hr 5.2 TB/hr 864 GB/hr 10.4 TB/hr	432 GB/hr 5.2 TB/hr 864 GB/hr 10.4 TB/hr	864 GB/hr 10.4 TB/hr 1.7 TB/hr 20.7 TB/hr	288 GB/hr 3.5 TB/hr 576 GB/hr 7.0 TB/hr	288 GB/hr 3.5 TB/hr 576 GB/hr 7.0 TB/hr	576 GB/hr 7.0 TB/hr 1.2 TB/hr 14 TB/hr
PHYSICAL • Dimensions (H x W x D) • Base configuration as shipped		76 x 24 x 41.5 in 193 x 61 x 105 cm 705 lb.			76 x 24 x 41.5 in 193 x 61 x 105 cm 705 lb.	
CONNECTIVITY • SCSI • Fibre channel • iSCSI		LVD std. Native 4 GB std. Optional			LVD std. Native 2 GB std. Optional	
OPERATIONAL SPECIFICATIONS • Mount time • Dismount time • Inventory time (80 cartridges) • Inventory time (500 cartridges)		<20 seconds <20 seconds <25 seconds <5 minutes			<20 seconds <20 seconds <25 seconds <5 minutes	
RELIABILITY SPECIFICATIONS • MTBF • MSBF • MTRR		>250,000 hours >2,00,000 cartridge swaps <15 minutes			>250,000 hours >2,00,000 cartridge swaps <15 minutes	
AGENCY CERTIFICATIONS	NTRL (US & Canada), CE, TUV, FCC, IC, CE, VCCCI, BSMI			NTRL (US & Canada), CE, TUV, FCC, IC, CE, VCCCI, BSMI		
POWER • Voltage • Frequency • Watts (typical)		100-240 VAC 47-63 Hz 638 watts			100-240 VAC 47-63 Hz 638 watts	

WORLDWIDE HEADQUARTERS

4820 Overland Avenue
San Diego, CA 92123 USA
Tel 1-800-729-8725
1-858-571-5555
Fax 1-858-571-3664
Email sales@overlandstorage.com

UNITED KINGDOM (EMEA OFFICE)

Overland House
Ashville Way
Wokingham, Berkshire
RG41 2PL England
Tel +44 (0) 118-9898000
Fax +44 (0) 118-9891897
Email europe@overlandstorage.com

FRANCE OFFICE

Overland Storage
13 rue Camille Desmoulins
92441 Issy les Moulineaux Cedex
France
Tel +33 (0) 1 58042550
Fax +33 (0) 1 58042636
Email europe@overlandstorage.com

GERMANY OFFICE

Humboldtstr. 12
85609 Dornach Germany
Tel +49-89-94490-214
Fax +49-89-94490-414
Email europe@overlandstorage.com

ASIA PACIFIC OFFICE

Overland Storage
Level 44, Suntec Tower Three
8 Temasek Boulevard
Singapore 038988
Tel +65 6866-3848
Fax +65 6866-3838
Email asia@overlandstorage.com